

Sterling®

DELUXE VINYL SIDING

Hand-Sawn Embossed Woodgrain Pattern



Single 8"

AVAILABLE IN WHITE ONLY

WHITE

SINGLE 8"

8" exposure per panel
12' 6" long
24 pcs. per ctn.
2 squares per ctn.



- ▶ **XLok®** Technology and the Norandex proprietary **NailRIGHT®** Siding Installation System, help ensure the siding is securely interlocked and properly affixed to the wall
- ▶ Hand-sawn embossed woodgrain pattern
- ▶ Wind load, test pressure 33.3 psf, 160 mph*
- ▶ 5/8" Panel projection
- ▶ Available in Single 8"
- ▶ .048" panel thickness
- ▶ Matching and contrasting soffit and accessories
- ▶ Limited Lifetime Transferable Warranty with **ColorHold®** Lifetime Fade Protection

*THE TEST PRESSURES LISTED ON NORANDEX VINYL SIDING ARE DERIVED FROM TESTING PER ASTM D-5206 WITH NAILS 16" ON CENTER. THE REPORTED WIND SPEEDS ARE CALCULATED UNDER ONE SET OF CONDITIONS. PLEASE CHECK WITH YOUR LOCAL BUILDING INSPECTOR FOR WIND LOAD REQUIREMENTS IN YOUR AREA AND FOR THE TYPE OF STRUCTURE IN WHICH THE SIDING IS BEING INSTALLED.




NORANDEX™
VINYL SIDING, SOFFIT & ACCESSORIES

WWW.NORANDEX.COM