



upgrade your view

- High performance in a builder's window
- Traditional or contemporary frame design
- SDL or GBG grilles
- Sizes to meet your need
- Egress Size: 3050SH, 4040SL
- Limited Lifetime Warranty

window anatomy

Multi-chamber construction with fusion-welded sash and frame

7/8" or 1" dual or triple pane insulated glass with Warm Edge spacer saves energy

Sloped sill drains water away from home exterior

Integral J-channel for simple, secure siding installation (optional double utility trim)



When you build a lot of homes, you expect a lot from your windows. Quality. Performance. Value. A company you can count on. Our new 500 single hung vinyl windows offer all that and more, including a full range of options to meet your every need.

easyinstall

for a quick, correct fit

- Alignment clips
- Double utility trim
- Integral J-channel
- Jamb extensions or drywall receiver options
- Accessory grooves
- Protective construction film



Optional LC 50 upgrade available in limited sizes

www.norandex.com

*Limited 10-year warranty for co-extruded color windows

500

perfeXion
by NORANDEX



Interior

Exterior



Jamb Alignment Clips

Aligns and holds frame in place during installation; enables one person to center smaller windows.



Removable Meeting Rail

Patented meeting rail anchor makes removing rail simple; ideal for drywall applications.



Integral Mulls

Twins and triples with continuous head and sill frame allows a mix of operating and fixed windows.



Interlocking Sash

Sash locks tightly together to help keep out intruders and inclement weather.



Forced Entry Resistant Locks

Enhanced security locks meet tough AAMA forced entry requirements. ADA accessible and auto-lock options available.



ADA Accessible Lock



Auto Lock

COLOR OPTIONS

Solid Vinyl



White

Beige

Clay

Co-extruded Colors*



*Black Co-extruded only available on single hung, sliding, fixed, and geometric windows

Painted Colors



Casement, Awning, Fixed Casements

GRID TYPES

(Also available with no grids)

GBG



3/4" Flat or
5/8" Sculptured

SDL



7/8" or 1 1/4" SDL
with Shadow Bar

FRAME TYPES

Brickmould



Beveled




Flat



GLASS OPTIONS

Compare U-Factor ratings



LOW-E

7/8" Low-E .35 SHGC .27
One lite of Low-E

7/8" Low-ESC .35 SHGC .22
One lite of solar cooling Low-E

7/8" Low-E2+ .30 SHGC .27
One lite of Low-E and one lite of Interior Surface Low-E



LOW-E with ARGON

7/8" HP .31 SHGC .27
One lite of Low-E with argon

7/8" HPSC .31 SHGC .22
One lite of solar cooling Low-E with argon

7/8" HP2+ .27 SHGC .26
One lite of Low-E and one lite of Interior Surface Low-E with argon

HP2+PSL .29 SHGC .50
One lite of passive solar low-E and one lite of Interior Surface Low-E with argon



TRIPLE-GLAZED

7/8" HP2Max .27 SHGC .26
Two lites of Low-E with two chambers of argon

7/8" HP3Max .24 SHGC .23
Two lites of Low-E, two chambers of argon, one lite of Interior Surface Low-E

Values reflect 3050 call size brickmould non-drywall glazed single window with 3mm glass, WarmEdge Spacer, no grilles. Beveled frame thermal values may differ slightly.

Optional foam fill is available for 500 Single Hung, Sliding, and Picture Windows with brickmould or bevel frames for greater thermal efficiency



NAMI LABEL CERTIFICATION

Highest level of testing for quality and performance



When choosing windows for their energy efficiency, it is important to select a glass package that meets the performance requirements for your climate zone. All of PerfeXion by Norandex innovative glass packages offer exceptional energy efficiency and are designed to accommodate the particular needs of homeowners throughout the United States.

PFXN500SS 82026 ADP



NORANDEX
EXTERIOR PRODUCTS FOR YOUR HOME

www.norandex.com